



INSULATE • TERMINATE • BUNDLE • IDENTIFY

NAMONKAR ENTERPRISES

NAMONKAR SILVER POLYESTER

High-Spec Labels

TECHNICAL DATA SHEET

Material

Silver Regular Polyester

Facestock

2 mil top coated matte finish metallic polyester face stock

Thickness: 50 microns \pm 10% (ISO 534)

Adhesive

General-purpose permanent rubber based adhesive featuring high initial tack and ultimate bond strength to a wide range of substrates.

Minimum Application Temperature: *(The minimum temperature at which the label can be applied and will adhere)*

- 5°C

Service Temperature Range: *(The temperature range to which the label can be exposed after the adhesion bond to the substrate has been formed)*

- 40°C to + 70°C

Liner

Super-calendered glassine paper with excellent strength characteristics

Basis Weight: 62 gsm + 10% (ISO 536)

Total Construction Caliper: 0.120 mm + 10%

Application and Use

Industrial*

Electrical equipment

- Transformers
- Control Panels
- Switchboards
- Other electrical machinery

Electronic equipment

Care should be taken if used on non-uniform surfaces

This material is designed for thermal-transfer printing

**Area in equipment where label is applied should be subject to only those temperature ranges specified above*

Shelf Life: Two years when stored at 22°C / 50% RH

Please test this product thoroughly under end-use conditions to make sure it meets the requirements of your specific application

**3, Raghunandan Complex, Mantarwadi Phata, Phursungi,
PUNE – 412308, Email – akrjain1202@gmail.com**