

Namonkar SL

GENERAL DESCRIPTION:

Namonkar SL is an excellent solution for wire and cable identification. This label has good clarity, conformability. Namonkar SL is designed to adhere to highly curved surfaces, wires and cables. It features a white printable area with clear "tail" that wraps around the marker. The clear tail serves as an over-laminate to protect the text, providing superior resistance to abrasion, dirt, oils, solvents, water and excessive handling.



| PRODUCT DATA | | VALUE | | | TEST METHOD |
|----------------------------|----------------|---------|---------|-----------|--|
| Physical Properties | | | | | |
| Thickness mil (micron) | Film: | 3.5 | (89) | ±10 % | ASTM D 3652 |
| | Adhesive: | 0.8-0.9 | (20-23) | ± 0.1 (3) | |
| | Liner: | 3.1 | (79) | ± 10 % | |
| Dimensional Stability (%) | MD: | 0.5 | | | On Al panel at 71°C for 24 hrs |
| | TD: | 0.5 | | | |
| Adhesion Properties | | | | | |
| Adhesion from | Average N/m | | | | ASTM D 903 (Modified for 72 hrs dwell time) |
| Stainless Steel | 539 | | | | |
| Acrylic | 858 | | | | |
| Glass | 550 | | | | |
| Polypropylene | 88 | | | | |
| Tack (gm) | 250 | | | | |

The data mentioned in this sheet are only guidelines and should not be used for setting specifications. The data in this document are for general information only.



NAMONKAR ENTERPRISES

INSULATE • TERMINATE • BUNDLE • IDENTIFY

Performance properties:

| | |
|--|--------------------------------------|
| Service Temperature Range | -40°C to 80°C |
| Minimum Application Temperature | 10°C |
| Storage Stability | Six months stored at 21°C and 50% RH |



INSULATE • TERMINATE • BUNDLE • IDENTIFY

NAMONKAR ENTERPRISES

The data mentioned in this sheet are only guidelines and should not be used for setting specifications. The data in this document are for general information only.